



Sauer Compressors



HAUG



Oil-free piston compressor

- 2.0–7.5 kW
- Suction pressure max. 14 bar(abs)
- Final pressure max. 101 bar(abs)
- 50–100 Nm³/h
- Gas-tight with magnetic coupling

HAUG. *Neptune*



OIL FREE



ZERO LEAKAGE



HIGH EFFICIENCY

Dependable up to 500 bar – anywhere, anytime, anygas.

The HAUG Sauer Kompressoren AG based in St. Gallen, Switzerland, is within the Sauer Compressors Group the competence center for oil-free and gas-tight piston compressors. These are developed and manufactured in St. Gallen for worldwide use.



Find your contact for sales and services below
www.sauercompressors.com

For further information about our products and applications please visit our website www.haug.ch



We reserve the right to make technical changes at any time without prior notice.

HAUG.Neptune compressors – oil-free and gas-tight

Power range 2.0 – 7.5 kW

The HAUG.Neptune series is used for the compression of any gas. Through the use of magnetic coupling, individual customer specifications and explosion proof requirements can be met.

HAUG.Neptune compressors with magnetic coupling are a HAUG Sauer development that provides permanent gas-tight compression without leakage. This hermetically sealed and entirely wear-free drive was first employed in a piston compressor in 1989 and can be used for suction pressures up to 14 bar(abs).

The modular HAUG.Neptune compressor concept allows highly individual and cost-effective adaptation of the compressor configuration to the customers requirements. This allows development of technically, commercially and energetically optimised solutions.

Features

- Completely oil-free and dry-running piston compressor
- Permanently technically tight with magnetic coupling
- Environmentally friendly because it is oil-free, gas-tight and efficient
- Compressor leak rate < 0.001 mbar 1/s
- Air-cooled
- Motor power from 2.0 to 7.5 kW
- Rotary speed range 970 to 1450 1/min
- Intake pressure max. 14 bar(abs)
- Final discharge pressure max. 101 bar(abs)
- Modular cylinder configuration with cylinder diameter up to 100 mm
- Version with 2 or 3 cylinders with 1-, 2- or 3-stages compression
- Maximum flow rate at atmospheric intake pressure approx. 50 Nm³/h
- Booster-version flow rate max. approx. 100 Nm³/h
- Explosion-proof compressor (conform with ATEX zone 1 or zone 2)
- Very robust and long-lasting construction
- Compact and foundation-free installation

Applications

Process compressors for any gas in various applications:

- Chemical industry
- Pharmaceutical industry
- Compression of medical gases
- Electronic industry
- Glass and steel industry
- Foodstuff industry
- Beverage industry
- Research & Development
- Gas recovery
- Gas production and gas storage
- Nitrogen inert gas supply

